


ダクタイトル 鋳鉄バルブ



分類		ゲートバルブ														
クラス	10 K						16 K									
形状																
本体材料	FCD-S															
要部材料	ステンレスCR13															
製品記号	10-DSR-N				10-DSRF-N				10-DSRF-N(BB)				16-DSR-N			
呼び径	L	H	D ₁	¥	L	H	D ₁	¥	L	H	D ₁	¥	L	H	D ₁	¥
10A(3/8B)	60	150	60	9,730	90	164	70	26,500					65	163	70	21,500
15(1/2)	70	171	70	12,800	100	165	70	27,500					75	182	80	25,200
20(3/4)	75	198	80	17,000	110	188	80	35,300					80	212	90	29,200
25(1)	85	233	90	25,200	120	219	90	43,300					90	245	100	37,200
32(1 1/4)	95	274	100	32,700	130	253	100	54,100					100	285	115	45,800
40(1 1/2)	105	318	115	46,900	140	285	115	77,600	178	352	200	91,000	110	330	135	59,300
50(2)									190	410	200	110,000				
65(2 1/2)									203	479	250	141,000				
80(3)									229	566	250	172,000				
100(4)									254	667	300	249,000				
125(5)									267	779	300	271,000				
150(6)									292	969	350	378,000				
200(8)									330	1181	400	600,000				
250(10)									356	1404	450	802,000				
300(12)																
最高許容圧力	-10~220°Cの STEAM, PL, GAS, AIR 1.0MPa -10~120°Cの H 1.4MPa				300°C以下の STEAM, PL, GAS, AIR 1.0MPa -10~220°Cの STEAM, PL, GAS, AIR 1.2MPa -10~120°Cの H 1.4MPa				-10~220°Cの GAS 1.6MPa -10~220°Cの STEAM, PL, GAS, AIR 2.0MPa -10~120°Cの H 2.2MPa							
備考	☆2009.3月より設計変更				●高圧ガス保安法に定める毒性ガス(ホスゲン・シアン化水素)を除く。 ●蒸気・高温水ラインに好適。											

分類		グローブバルブ																		
クラス	10 K																			
形状																				
本体材料	FCD-S																			
要部材料	ステンレスCR13																			
製品記号	10-DG-N				10-DGF-N				10-DGF-N(BB)				10-DD-N				10-DDF-N			
呼び径	L	H	D ₁	¥	L	H	D ₁	¥	L	H	D ₁	¥	L	H	D ₁	¥	L	H	D ₁	¥
8A(1/4B)	50	108	60	4,680									55	108	60	5,270				
10(3/8)	55	108	60	4,680									65	123	70	5,540	85	123	70	13,500
15(1/2)	65	122	70	4,910	85	122	70	12,100					80	123	80	6,960	95	123	80	16,000
20(3/4)	80	125	80	5,930	95	125	80	13,100					90	144	90	8,850	110	144	90	22,700
25(1)	90	146	90	7,330	110	146	90	18,300					105	159	100	14,600	130	159	100	30,100
32(1 1/4)	105	160	100	13,400	130	160	100	25,800					120	178	115	20,600	150	178	115	37,700
40(1 1/2)	120	180	115	17,200	150	180	115	32,900	203	302	200	93,200	140	197	135	29,900	180	197	135	49,600
50(2)	140	198	135	25,100	180	198	135	41,900	216	317	225	113,000								
65(2 1/2)									241	356	250	136,000								
80(3)									292	377	250	185,000								
100(4)									356	460	300	314,000								
125(5)									406	524	350	390,000								
150(6)									495	585	400	633,000								
200(8)									622	880	360									
250(10)																				
最高許容圧力	-10~220°Cの STEAM, PL, GAS, AIR 1.0MPa -10~120°Cの H 1.4MPa				300°C以下の STEAM, PL, GAS, AIR 1.0MPa -10~220°Cの STEAM, PL, GAS, AIR 1.2MPa -10~120°Cの H 1.4MPa				-10~130°Cの STEAM, PL, GAS, AIR 1.0MPa -10~120°Cの H 1.4MPa											
備考	●高圧ガス保安法に定める毒性ガス(ホスゲン・シアン化水素)を除く。				●蒸気・高温水ラインに好適。 ☆2009.3月より設計変更、10-DG-N 呼び径8A追加 250Aはギア操作式です															

(本体防錆塗装付 アクリル変性アルキド樹脂塗装(シルバー色))

