


ダクティル 鋳鉄バルブ

分類		ゲートバルブ															
クラス		10 K										16 K					
形状																	
																	
		公共建築工事標準仕様書相当品		公共建築工事標準仕様書相当品		公共建築工事標準仕様書相当品		公共建築工事標準仕様書相当品									
本体材料		FCD-S															
要部材料		ステンレスCR13															
製品記号	10-DSR-N				10-DSRF-N				10-DSRF-N(BB)				16-DSR-N				
呼び径	L	H	D ₁	¥	L	H	D ₁	¥	L	H	D ₁	¥	L	H	D ₁	¥	
10A(3/8B)																	
15(1/2)	60	150	60	9,730	90	164	70	26,500						65	163	70	21,500
20(3/4)	70	171	70	12,800	100	165	70	27,500						75	182	80	25,200
25(1)	75	198	80	17,000	110	188	80	35,300						80	212	90	29,200
32(1 1/4)	85	233	90	25,200	120	219	90	43,300						90	245	100	37,200
40(1 1/2)	95	274	100	32,700	130	253	100	54,100						100	285	115	45,800
50(2)	105	318	115	46,900	140	285	115	77,600	178	352	200	91,000	110	330	135	59,300	
65(2 1/2)									190	410	200	110,000					
80(3)									203	479	250	141,000					
100(4)									229	566	250	172,000					
125(5)									254	667	300	249,000					
150(6)									267	779	300	271,000					
200(8)									292	969	350	378,000					
250(10)									330	1181	400	600,000					
300(12)									356	1404	450	802,000					
最高許容圧力	-10~220℃の STEAM (P), GAS (AIR) 1.0MPa				300℃以下の STEAM (P), GAS (AIR) 1.0MPa								-10~220℃の GAS 1.6MPa				
	-10~120℃の H 1.4MPa				-10~220℃の STEAM (P), GAS (AIR) 1.2MPa								-10~220℃の STEAM (P), GAS (AIR) 2.0MPa				
					-10~120℃の H 1.4MPa								-10~120℃の H 2.2MPa				
備考	☆2009.3月より設計変更				●高圧ガス保安法に定める毒性ガス(ホスゲン・シアン化水素)を除く。				●蒸気・高温水ラインに好適。								

分類		グ ロ ー ブ バ ル ブ																		
クラス		10 K																		
形状	 国土 (1/2~2B) 納入図 CAD	 国土 納入図 CAD	 国土 (65~200A) 納入図 CAD	 国土 (1/2~2B) 納入図 CAD	 国土 納入図 CAD															
	公共建築工事標準仕様書相当品					公共建築工事標準仕様書相当品			公共建築工事標準仕様書相当品			公共建築工事標準仕様書相当品			公共建築工事標準仕様書相当品					
本体材料		FCD-S																		
要部材料		ステンレスCR13																		
製品記号	10-DG-N				10-DGF-N				10-DGF-N (BB)				10-DD-N				10-DDF-N			
呼び径	L	H	D ₁	¥	L	H	D ₁	¥	L	H	D ₁	¥	L	H	D ₁	¥	L	H	D ₁	¥
8A(1/4B)	50	108	60	4,680																
10(3/8)	55	108	60	4,680									55	108	60	5,270				
15(1/2)	65	122	70	4,910	85	122	70	12,100					65	123	70	5,540	85	123	70	13,500
20(3/4)	80	125	80	5,930	95	125	80	13,100					80	123	80	6,960	95	123	80	16,000
25(1)	90	146	90	7,330	110	146	90	18,300					90	144	90	8,850	110	144	90	22,700
32(1 1/4)	105	160	100	13,400	130	160	100	25,800					105	159	100	14,600	130	159	100	30,100
40(1 1/2)	120	180	115	17,200	150	180	115	32,900					120	178	115	20,600	150	178	115	37,700
50(2)	140	198	135	25,100	180	198	135	41,900	203	302	200	93,200	140	197	135	29,900	180	197	135	49,600
65(2 1/2)									216	317	225	113,000								
80(3)									241	356	250	136,000								
100(4)									292	377	250	185,000								
125(5)									356	460	300	314,000								
150(6)									406	524	350	390,000								
200(8)									495	585	400	633,000								
250(10)									622	880	360	○								
最高許容圧力	-10~220℃の STEAM (P), GAS (AIR) 1.0MPa -10~120℃の H 1.4MPa ☆2009.3月より設計変更、10-DG-N 呼び径8A追加								300℃以下の STEAM (P), GAS (AIR) 1.0MPa -10~220℃の STEAM (P), GAS (AIR) 1.2MPa -10~120℃の H 1.4MPa 250Aはギア操作式です (製品記号:10-DGF-N-W/GB)				-10~130℃の STEAM (P), GAS (AIR) 1.0MPa -10~120℃の H 1.4MPa							
備考	●高圧ガス保安法に定める毒性ガス(ホスゲン・シアン化水素)を除く。 ●蒸気・高温水ラインに好適。																			

〈本体防錆塗装付 アクリル変性アルキド樹脂塗装(シルバー色)〉

ダクタイル 鋳鉄バルブ



分 類		ゲ ー ト バ ル ブ																		
ク ラ ス		16 K								20 K										
形 状																				
	国土 納入図	国土 (65~300A) 納入図	国土 納入図	国土 納入図	国土 (65~300A) 納入図							国土 納入図	国土 (65~300A) 納入図							
公 共 建 築 工 事 標 準 仕 様 書 相 当 品	公 共 建 築 工 事 標 準 仕 様 書 相 当 品								公 共 建 築 工 事 標 準 仕 様 書 相 当 品								公 共 建 築 工 事 標 準 仕 様 書 相 当 品			
本 体 材 料	FCD-S																			
要 部 材 料	ステンレスCR13																			
製 品 記 号	16-DSRF-N				16-DSRF-N(BB)				20-DSR-N				20-DSRF-N				20-DSRF-N(BB)			
呼 び 径	L	H	D ₁	¥	L	H	D ₁	¥	L	H	D ₁	¥	L	H	D ₁	¥	L	H	D ₁	¥
10A(3/8B)																				
15(1/2)	108	163	70	31,100					70	175	90	31,700	108	175	90	41,400				
20(3/4)	117	164	70	31,400					75	177	90	36,300	117	177	90	43,100				
25(1)	127	187	80	36,300					85	214	100	42,800	127	214	100	51,700				
32(1 1/4)	140	219	90	45,700					95	241	115	50,100	140	241	115	60,000				
40(1 1/2)	165	253	100	52,200					105	277	135	57,200	165	277	135	69,100				
50(2)	178	285	115	68,400	178	352	200	108,000	115	301	135	68,100					216	395	200	116,000
65(2 1/2)					190	410	200	131,000									241	450	200	147,000
80(3)					203	479	250	172,000									283	520	250	182,000
100(4)					229	566	250	210,000									305	595	250	246,000
125(5)					254	667	300	335,000									381	725	300	456,000
150(6)					267	779	300	412,000									403	820	350	469,000
200(8)					292	993	350	615,000									419	1070	400	723,000
250(10)					330	1181	400	824,000									457	1247	450	959,000
300(12)					356	1404	450	1,206,000									502	1451	500	1,369,000
最 許 容 圧 力	-10~220℃の STEAM (P) 2.0MPa -10~220℃の GAS 1.6MPa -10~120℃の H 2.2MPa				350℃以下の STEAM (P) 1.6MPa 300℃以下の STEAM (P) 1.8MPa -10~220℃の STEAM (P) 2.0MPa -10~120℃の H 2.2MPa				350℃以下の STEAM (P) 2.0MPa -10~220℃の GAS 2.4MPa -10~120℃の H 2.8MPa				300℃以下の STEAM (P) 2.3MPa -10~220℃の STEAM (P) 2.5MPa -10~120℃の H 2.8MPa							
	● 高圧ガス保安法に定める毒性ガス(ホスゲン・シアン化水素)を除く。 ☆ 2009.3月より設計変更				● 蒸気・高温水ラインに好適。 ☆ 2006.3月より設計変更				● 蒸気・高温水ラインに好適。 ☆ 2009.3月より設計変更(20-DSRF 呼び径50A中止)											
備 考																				

分類		グ ロ ー ブ バ ル ブ																														
ク ラ ス		16 K								20K																						
形 状	 国土 納入図	 国土 納入図	 国土 (65~200 ^A) 納入図 CAD (80~200 ^A)	 TOYO 国土 (1/2~25) 納入図	 TOYO 国土 (15~50 ^A) 納入図	 国土 (65~200 ^A) 納入図																										
							公共建築工事標準仕様書相当品																									
本体材料		FCD-S																														
要部材料		ステンレスCR13																														
製品記号	16-DG-N				16-DGF-N				16-DGF-N(BB)				20-DG-N				20-DGF-N				20-DGF-N(BB)											
呼 び 径	L	H	D ₁	¥	L	H	D ₁	¥	L	H	D ₁	¥	L	H	D ₁	¥	L	H	D ₁	¥	L	H	D ₁	¥								
10 ^A (3/8 ^B)	70	122	80	14,500	108	122	80	20,700					75	136	70	14,900	110	136	70	21,400												
15(1/2)	85	128	80	16,500	117	128	80	24,900					78	138	80	16,200	110	138	80	22,900												
20(3/4)	95	147	100	21,900	127	146	100	31,100					91	157	100	19,400	120	157	100	28,800												
25(1)	110	165	115	33,800	140	165	115	39,800					105	178	115	23,600	130	178	115	37,700												
32(1 1/4)	125	182	115	38,100	165	182	115	47,100					122	202	135	37,700	160	202	135	45,600												
40(1 1/2)	145	196	135	50,300	203	198	135	65,700					135	210	135	45,400	180	210	135	56,400												
50(2)									203	302	200	103,000									267	243	225	145,000								
65(2 1/2)									216	313	225	135,000									292	347	250	156,000								
80(3)									241	356	250	159,000									318	382	250	173,000								
100(4)									292	377	250	214,000									356	457	300	236,000								
125(5)									356	460	300	378,000									400	534	350	428,000								
150(6)									406	524	350	520,000									444	593	400	537,000								
200(8)									495	585	400	825,000									559	697	560	863,000								
250(10)																																
300(12)																																
最 許 容 圧 力 ● 備 考	-10~220℃の STEAM (P) (AIR) 2.0MPa -10~220℃の GAS 1.6MPa -10~120℃の H 2.2MPa								350℃以下の STEAM (P) (AIR) 1.6MPa 300℃以下の STEAM (P) 1.8MPa -10~220℃の STEAM (P) 2.0MPa -10~120℃の H 2.2MPa								350℃以下の STEAM (P) (AIR) 2.0MPa -10~220℃の GAS 2.4MPa -10~120℃の H 2.8MPa								300℃以下の STEAM (P) (AIR) 2.3MPa -10~220℃の STEAM (P) (AIR) 2.5MPa							
	●高圧ガス保安法に定める毒性ガス(ホスゲン・シアン化水素)を除く。 ☆2009.3月より設計変更								●蒸気・高温水ラインに好適。 ☆2006.3月より設計変更								●蒸気・高温水ラインに好適。 ☆2009.3月より設計変更															

(本体防錆塗装付 アクリル変性アルキド樹脂塗装(シルバー色))